

In The United States Patent And Trademark Office

Applicant: Jaakko Haapanen Date: May 14, 2005
Date Filed: Simultaneously herewith Docket No.: FORSAL-104
PCT App. No.: PCT/FI2003/000853
For: Core Locking Device


Certificate of Express Mailing

I hereby certify that this document is being deposited with
the United States Postal Service "Express Mail Post Office to
Addressee" service under 35 C.F.R. §1.10

on May 14, 2005

with Mailing Label No. EV 728 023 765 US

and is addressed to the Commissioner for Patents, P.O. Box
1450, Alexandria, VA 22313-1450



Signature

David R. J. Stiennon, Reg. No. 33212

Name of applicant, assignee or Registered Representative

Submission of Substitute Specification Under 37 C.F.R. § 1.125

Commissioner for Patents
P.O. Box 1450, Alexandria, VA 22313-1450


Dear Sir:

A substitute specification, excluding the claims, is filed herewith under the provisions of 37 C.F.R. § 1.125(b).

1. The substitute specification contains no new matter.
2. A marked-up copy of the substitute specification showing the matter being added to and the matter being deleted from the specification of record accompanies this paper. The matter being added is underlined and bold, and the matter being deleted is shown struck out, enclosed in brackets and bold.
3. The substitute specification is submitted in clean form without markings as to amended material.

Applicant requests that the accompanying substitute specification be entered in the application record.

Respectfully submitted,



David R. J. Stiennon, Reg. No. 33212

Attorney for Applicant

Stiennon & Stiennon

612 W. Main St., Suite 201, P.O. Box 1667

Madison, Wisconsin 53701-1667

(608) 250-4870

In The United States Patent And Trademark Office

Applicant: Jaakko Haapanen

Date: May 14, 2005

Date Filed: Simultaneously herewith

Docket No.: FORSAL-104

PCT App. No.: PCT/FI2003/000853

For: Core Locking Device


Certificate of Express Mailing

I hereby certify that this document is being deposited with
the United States Postal Service "Express Mail Post Office to
Addressee" service under 35 C.F.R. §1.10

on May 14, 2005

with Mailing Label No. EV 728 023 765 US

and is addressed to the Commissioner for Patents, P.O. Box
1450, Alexandria, VA 22313-1450



Signature

David R. J. Stiennon, Reg. No. 33212

Name of applicant, assignee or Registered Representative

Clean Copy of Substitute Specification under 37 C.F.R. 1.125(c)

TITLE OF THE INVENTION

Core Locking Device

CROSS REFERENCES TO RELATED APPLICATIONS

[0001] This application is a U.S. national stage application of International App. No. PCT/FI2003/000853, filed Nov. 11, 2003, the disclosure of which is incorporated by reference herein, and claims priority on Finnish App. No. 20022037, Filed Nov. 15, 2002.

5

STATEMENT AS TO RIGHTS TO INVENTIONS MADE UNDER
FEDERALLY SPONSORED RESEARCH AND DEVELOPMENT

[0002] Not applicable.

BACKGROUND OF THE INVENTION

[0003] The invention relates to core locking devices.

[0004] In the prior art, slitter-winders are known in which two-drum winders are used for winding component rolls after slitting a web. In the prior art there are
5 known variable geometry two-drum winders in which one or both of the winding drums/sets of drums supporting the roll are movable. In such variable geometry slitter-winders, the horizontal location of the center of the roll that is building up is dependent on the relative position of the winding drums/sets of drums and on the diameter of the roll. In winders, rolls are wound around cores. Longitudinal
10 successive cores are locked in place to form a core line by means of a core locking device placed at both ends. In the prior art, a core locking device is known which is placed on a slide arranged in connection with a winder so as to be movable when the diameter of the roll increases as its center is displaced. Thus, the position of the core locking device changes during operation. The position of the core locking device
15 that moves upwards on the slide also changes when the pivoting angle changes while in the variable geometry winder one or both drums move as winding progresses. When the core locking device pivots, the pivoted core locking device causes a force in the center of the roll, which force is dependent on the pivoting angle and on the mass of the device. This may cause problems during winding because the magnitude
20 of the force cannot be affected.

[0005] In addition, in the prior art two-drum winders, mechanical guides, which limit the utilization of space, have been used for set change for guiding the core locking device to a correct position according to core size.

[0006] One problem with winding is also the so-called bouncing phenomenon in
25 which a roll/rolls start bouncing in the winder.

SUMMARY OF THE INVENTION

[0007] An object of the invention is to provide a core locking device in which the changing of the position of the core chuck as winding progresses does not cause winding problems nor a force acting on the center of the roll.

5 [0008] A non-indispensable further object of the invention is to provide an arrangement in which no mechanical guides limiting the utilization of space are needed for set change in the two-drum winder. Further, a non-indispensable additional feature of the invention is to create an arrangement which makes it possible to detect the occurrence of a bouncing phenomenon and, when needed, to
10 eliminate it.

[0009] In accordance with the invention, an actuator is placed in connection with the core locking device, preferably in connection with a pivot joint of the core locking device, which actuator produces a counterforce that is equal to the force caused by the mass of the core locking device in the changed position of the core
15 chuck. In that connection, the core locking device is "weightless" at all pivoting angles, thus not affecting winding and the structure of the roll. The force caused by mass can be static and/or dynamic.

[0010] During set change, in the device in accordance with the invention, the device is driven by means of a relief actuator to a correct position depending on core
20 size. When the roll positions, diameters and the core diameter are known, the position of the core center can be calculated.

[0011] The invention can also be made use of in case it is desired to measure the effect of horizontal forces on the winding process or to tune the actuator to function either as an active damper or as a passive damper. Passive damping can be
25 accomplished, for example, when using a hydraulic actuator, such that flow is throttled or flow is restricted, i.e. the damping of the system is changed. In active damping, the position/pressure of the actuator is measured and the variable that

determines the action of the actuator is changed based on the result of measurement.

[0012] In accordance with an advantageous additional application of the invention, the device can be used for detecting the bouncing phenomenon when an angle sensor that measures the pivoting angle is placed in connection with the actuating member;
5 the bouncing phenomenon can be detected based on the measurements of the angle sensor and, when needed, a counterforce can be produced by means of the actuator to eliminate the bouncing phenomenon.

[0013] In addition, in two-drum winders which use as one winding drum a set of drums with a belt disposed around it, the device in accordance with the invention
10 makes it possible to compensate for the change of the starting position of winding caused by wear of the belt. Wear of the belt affects the location of the core and thus also the location of the locking device. When the locking device is lowered onto the drums, the device can be "calibrated" and wear of the belt can also be inferred from the starting position.

[0014] The invention is particularly suitable for two-drum winders in which the
15 rear winding drum is arranged to be movable. In two-drum winders the movement of the rear drum makes it possible to affect the winding properties and achieve quick set change.

[0015] In accordance with the invention, the state of the actuating member is
20 advantageously measured in the center of a joint, for example, by means of an angle sensor placed at the end of the joint or by means of a distance measuring sensor or a force sensor placed inside the actuator, preferably a cylinder, thus making it possible to produce a counterforce of desired magnitude in order that the force caused by the core chuck in the center of the roll shall not cause winding problems.

[0016] In the following, the invention will be described in greater detail with reference to the figures of the appended drawing, but the invention is by no means meant to be narrowly limited to the details of them.

BRIEF DESCRIPTION OF THE DRAWINGS

[0017] FIGS. 1A and 1B schematically show a variable geometry two-drum winder and a core locking device placed in connection therewith, in extreme positions of the core locking device.

5 [0018] FIGS. 2A and 2B schematically show extreme positions of the core locking device in accordance with one exemplifying embodiment of the invention.

[0019] FIG. 3 schematically shows the core locking device in accordance with one application of the invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0020] As shown in Figs. 1A and B, a paper roll 10 is wound on a two-drum winder which, in the application shown in the figures, is formed of a set of belt drums 11 in which an endless belt 14 is placed around two drums 12, 13. The other
5 set of drums of the two-drum winder is formed of a drum 15.

[0021] FIGS. 1A and B show two different phases of winding, of which the situation occurring in the end phases of winding is shown in FIG. 1A and the situation occurring in the initial phase of winding is shown in FIG. 1B.

[0022] At the beginning of winding, as shown in FIG. 1B, a core locking device,
10 i.e. a core chuck 17 is situated on a slide 16 in a lower position, and an arm 21 of the core locking device (FIG. 2) has not pivoted around a joint 24 (FIG. 2). In that connection, the core locking device 17 does not produce a force in the center 18 of the roll 10. When winding has made progress, FIG. 1A, the core locking device 17 moves with the center 18 of the roll being formed forwards on the slide 16, so that
15 the core locking device 17 will gradually be at an angle with respect to the slide 16, with the result that a force is produced in the center 18 of the roll 10 because of the weight of the core locking device 17.

[0023] In accordance with one application of the invention shown in FIGS. 2A and 2B, an actuator 20, advantageously a cylinder – the figure shows a hydraulic cylinder
20 arrangement but, for example, a semi-rotary actuator is also suitable – is placed in connection with the core locking device 17. As shown in the figure, when the pivoting angle α of the core chuck 17 increases, by means of the cylinder 20 a force is produced that acts on the center 18 of the core cancelling out the force caused by the pivoting angle α . A structure connected with the slides 16 of the core chuck 17 is
25 designated by 19 and the actuator 20 is attached to a pivot point 23 of the frame structure 19 and to a pivot point 26 of the pivoting arm 21 of the core chuck 17, which actuator 20 pivots when the angle α increases in a corresponding manner as the core chuck 17 pivots around the joint 24.

[0024] In FIG. 3, the parts of the core locking device or the core chuck 17 of the invention corresponding to those of FIGS. 2A and 2B are designated by the same reference signs. The actuator 20 in accordance with the invention, by means of which the force produced by the pivoted core chuck 17 in the center of the roll 10 is cancelled out, is attached through the pivot point 23 to the frame structure 19 of the core locking device 17, which frame structure 19 is connected to the slide 16 in the winder. In the figure, the locking member placed in the center 18 of the roll is designated by the reference numeral 25.

[0025] A sensor 27 is arranged in connection with the actuator 20 for detecting the pivoting angle α of the core locking device 17 to determine the magnitude of the necessary counterforce to be produced by means of the actuator 20 for cancelling out the force caused by the weight of the core locking device 17 at the angle α .

[0026] The invention is in accordance with an advantageous application, the bouncing phenomenon can be detected and eliminated by means of the actuator 20 and the sensor 27.

[0027] Above, the invention has been described only with reference to some of its advantageous exemplifying embodiments, but the invention is not by any means meant to be narrowly limited to the details of them.